

	MADINED	CVI	INIDE	R SLEEVES			LA Sleeve		Adv	anced Sle	eve
	IVIANIIVEN	CIL	יטווו.	IN SLEEVES		1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	O.D.	O.D.	O.D.	O.D.	0.D.	0.D.
18 HP	1984-95	2	AC	Straight Sleeve	2.559"		LA018		1072SA	1072SB	
20 HP	1984-00	2		With Ports	65mm		4-11/16"		4.690	4.690	
25 HP	1984-00	2					2-3/4"		2.753	2.773	
25 HP	1980-83	2	CI	Straight Sleeve	2.638"	T210	LA210	L210			
Crossflow				No Ports	67mm	5.00	5.00	5.00			
						2-3/4"	2-13/16"	2-7/8"			
30 HP	1980-84	2	RS	Straight Sleeve	2.835"		YA5025		3307SA		
				With Ports	72mm		4.925				
							3.077		3.075		
40 HP	1980-89	2	RS	Straight Sleeve	2.953"		LA044	L044	1076SA	1076SB	
50 HP	1990-91	2		With Ports	75mm		5-5/16"	5-5/16"	5.325	5.325	
	1000 01	-		With the	70111111		3.156	3.190	3.160	3.180	
60 HP	1980-83	2	RS	Straight Sleeve	3.228"		LA071	0.100	1035SA	1035SB	
(No. 6E9)	1300-03	4	INO	With Ports	82mm		5.556		5.565	5.565	
(NO. 0E9)				WILLIFOLS	02111111						
60 HP		2	DC	Cárcialat Clasura	3.307"		3.433		3.434	3.460	
		2	RS	Straight Sleeve			LA049				
(No. 6F0)				With Ports	84mm		5.556				
		+-	-				3.511				
70 HP		3	CI	Straight Sleeve	2-7/8"	T214	LA214 *	L214	1018SA	1018SB	
80 HP		4		No Ports		4-7/8"	4-7/8"	4-7/8"	4.875	4.875	
90 HP		6		Shorter Length		3.00	3-1/16"	3-1/8"	3.003	3.128	
115 HP		6		Longer Length		T216	LA216	L216			
						5.00	5.00	5.00			
						3.00	3-1/16	3-1/8"			
70 HP		3	CI	Straight Sleeve	2.875"	T017		L017	1021SA	1021SB	
115 HP	1980-85	6		With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				w/ Power Port		3.00		3-1/8"	3.003	3.128	
80 HP		4	CI	Straight Sleeve	2.875"	T019		L019	1022SA	1022SB	
				With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
						3.00		3-1/8"	3.003	3.128	
90 HP	1980-85	6	CI	Straight Sleeve	2.875"	T016		L016	1019SA	1019SB	
			'	With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				no power port		3.00		3-1/8"	3.003	3.128	
135 HP	1988-00	V6	CI	Straight Sleeve	3-1/8"	5.00	LA04	L04	1026SA	1026SB	
150 HP	1988-98	V6		With Ports	0 1/0		5.550	5.550	5.545	5.545	
175 HP	1980-82	V6					3-5/16"	3-3/8"	3.313	3.375	
1998cc (122 C.I.)	1000-02	1					3 3/10	3 3/0	0.010	0.010	
200 HP	1980-81	V6	AC	Straight Sleeve	3-3/8"		LA05		1048SA	1048SB	1044SC
200 HP 225 HP	1300-01	V6		With Ports	3-3/0				5.550		5.550
ZZJ NF		νo		Willi POILS			5.550			5.550	
475 UD	4000.00	1/0	100	O4:	0.0/0"		3-9/16"		3.565	3.585	3.628
175 HP	1982-92	V6		Straight Sleeve	3-3/8"		LA014		1027SA	1027SB	1027SC
200 HP EFI	1984-91	V6		With Ports			5.550		5.550	5.550	5.550
	hrome Cylinde	<u> </u>		w/finger ports		Oversize	3-9/16"		3.565	3.585	3.628

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS** Denotes Replacement Sleeve
 - CI Denotes Cast in Sleeve Liner

- ② Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - **CS** Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



	MERCURY	CYL	IND	ER SLEEVES			LA Sleeve		Adı	anced Sle	eve
						1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore Size	Length O.D.	Length O.D.	Length O.D.	Length O.D.	Length O.D.	Length O.D.
6 HP (12.8C.I.)		2	CI	Straight Sleeve	2.125"	T202	0.0.	L202	0.0.	0.0.	U.D.
8 HP		2	Ci	No Ports	54mm	4-9/16"		4-9/16"			
9.9 HP		2		INO FOILS	34111111	2-1/4"		2-3/8"			
10 HP	1984-85	2	۸٥	Straight Sleeve	2.559"	2-1/4	LA018	2-3/0	1072SA	1072SB	
18 HP	1984-95	2	AC	With Ports	65mm		4-11/16"		4.690	4.690	
20/25 HP				Willi Folis	OSIIIIII						
	1984-04	2					2-3/4"		2.753	2.773	
25XD (24.4 C.I.)	4005.00	-	D0	Otracials to Olassus	0.000			1.400			
30 HP	1995-03	2	K5	Straight Sleeve	2.992"			L129			
				With Ports	76mm			5.580			
		-				=		3.202			
35 HP		2	CI	Straight Sleeve	2-7/8"	T214		L214	1018SA	1018SB	
				No Ports		4-7/8"		4-7/8"	4.875	4.875	
						3.00		3-1/8"	3.003	3.128	
40 HP	1990-95	4	CI	Straight Sleeve	2-9/16"	T209		L209	1032SA	1032SB	
45 HP	1986-89	4		No Ports		4-3/8"		4-3/8"	4.688	4.688	
50 HP	1970-85	4				2-11/16"		2-13/16"	2.688	2.813	
Crossflow (Classic Series)										
40 HP	1994-04	2	RS	Straight Sleeve	2.992"			L160	1200SA	1200SB	
				With Ports	76mm			5.575	5.585	5.585	
				Notch Exh				3.200	3.200	3.220	
40 HP	1991-97	3		Straight Sleeve	2.955				1177SA	1177SB	
									5.280	5.280	
				With Ports					3.200	3.220	
50 HP	1984-90	3	CI	Straight Sleeve	2-7/8"	T017		L017	1021SA	1021SB	
60 HP	1984-90			With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				w/power port		3.00		3-1/8"	3.003	3.128	
50 HP	1991-97	3	RS	Straight Sleeve	2.953"			L085	1062SA	1062SB	1062S
60 HP	1991-97	3		With Ports	75mm			5.283	5.280	5.280	5.280
				w/Exhaust Notch				3.200	3.200	3.220	3.240
35 HP	1999	3	RS	Straight Sleeve	2.992"			L150	1115SA	1115SB	1115S
40 HP	1998-04	3		With Ports	76mm			5.585	5.585	5.585	5.585
50 HP	1998-04	3		w/Exhaust Notch				3.200	3.200	3.220	3.240
60 HP	1998-04	3							0.200		
50 HP	1998-04	3	RS	Straight Sleeve	2.992"		L150		1123SA		
60 HP	1998-00	3		With Ports			5.585		5.280		
00111	1330 00			2 finger ports			3.200		3.200		
50 HP	1999			Flanged sleeve	2.480"		0.200		1161FA		
OV 111	1333			4 Stroke	2.400				4.600		
				4 Stioke					2.680		
60 HP		3	CI	Straight Sleeve	2-7/8"	T214		L214	1018SA	1018SB	
65 HP	1972-76	3	U	No Ports		4-7/8"		4-7/8"	4.875	4.875	
					73mm						
70 HP	1977-83	3		Shorter Length		3.00	1.4040	3-1/8"	3.003	3.128	
75 HP 80 HP		4		Longer Length		T216	LA216	L216			
YN HD		4				5.00	5.00	5.00			

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - RS Denotes Replacement Sleeve
 - CI Denotes Cast in Sleeve Liner

- Oversizes Available
 - **CC** Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



	MEDCLIDA	CAI	INID	ER SLEEVES			LA Sleeve		Adv	vanced Sle	eve
	WIERCURY	CIL	וטאוו.	TK SLEEVES		1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	0.D.	0.D.	0.D.	O.D.	0.D.	0.D.
65 HP	1972-76	3	CI	Straight Sleeve	2-7/8"	T017		L017	1021SA	1021SB	
70 HP	1977-83	3		With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				w/power port		3.00		3-1/8"	3.003	3.128	
75 HP	1984-85	4	CI	Straight Sleeve	2-7/8"	T019		L019	1022SA	1022SB	
(Crossflow)				With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				w/power port		3.00		3-1/8"	3.003	3.128	
70 HP	1987-89	3	RS	Straight Sleeve	3.375"		LA050	L050	1050SA	1050SB	
75 HP	1990-93	3	CS	With Ports	86mm		5.490	5.490	5.770	5.770	
80 HP	1987-89			w/Exhaust Notch			3.642	3.670	3.642	3.662	
							(RS Sleeve)	(CS Sleeve)			
75 HP	1994-04	3	RS	Straight Sleeve	3.500"			L130	1101SA	1101SB	
90 HP	1994-04	3		With Ports	89mm			5.770	5.770	5.770	
				short exh notch: .535"				3.766	3.766	3.786	
75 HP	1998-04	3	RS	Straight Sleeve	3.500"			L167	1150SA		
90 HP	1998-04	3		With Ports	89mm			5.770	5.770		
				long exh notch: .930"				3.766	3.766		
75 HP Optimax		3		Straight Sleeve	3.622"			L193	1189SA	1189SB	
90 HP Optimax		3		With Ports	92mm				5.975		
115 HP Optimax		4							3.884		
80 HP	1968-74	4	CI	Straight Sleeve	2-7/8"	T021		L021	1043SA	1043SB	
Crossflow				With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
						3.00		3-1/8"	3.003	3.128	
80 HP	1978-84	4	CI	Straight Sleeve	2-7/8"	T019		L019	1022SA	1022SB	
85 HP	1975-77			With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				w/power port		3.00		3-1/8"	3.003	3.128	
85 HP	1987-93	3	RS	Straight Sleeve	3.375"		LA052	L052	1051SA	1051SB	
90 HP	1987-93	3	CS	With Ports	86mm		5.490	5.490	5.550	5.550	
				w/Exhaust Notch			3.642	3.670	3.642	3.662	
							(RS Sleeve)	(CS Sleeve)			
85 HP		4	CI	Straight Sleeve	2-7/8"	T214	LA214	L214	1018SA	1018SB	
90 HP		6		No Ports	73mm	4-7/8"	4-7/8"	4-7/8"	4.875	4.875	
100 HP		6		Shorter Length	[_	3.00	3-1/16"	3-1/8"	3.003	3.128	
115 HP		6		Longer Length	_[T216		T216			
150 HP		6				5.00		5.00			
						3.00		3-1/8"			
90 HP	1978-83	6	CI	Straight Sleeve	2-7/8"	T045		L045	1019SA	1019SB	
				With Ports	73mm	4-7/8"		4-7/8"	4.875	4.875	
				no power port		3.00		3-1/8"	3.003	3.128	
90 HP	1984-85	6	CI	Straight Sleeve	2.875"	T095		L095	1063SA	1063SB	
				With Ports	73mm	4-7/8"		4-7/8"			
				no power port		3.00		3-1/8"			
					3.118"				1185SA	1185SB	
90-115hp		'			0.110				11000/	110000	
90-115hp 4 Stroke					79mm				5.195	5.195	

- AC Denotes Alloy-Chrome Cylinder Bore
 - **RS** Denotes Replacement Sleeve
 - CI Denotes Cast in Sleeve Liner

- 2 Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.

	MFRCURY	CAI	INDI	ER SLEEVES			LA Sleeve		Adı	vanced Sle	eve
	- WILKCOKI	CIL				1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	0.D.	O.D.	0.D.	O.D.	O.D.	0.D.
90 HP	1987-93	3	RS	Straight Sleeve	3.375"		LA052	L052	1137SA	1137SB	
				With Ports			5.490	5.490	5.490	5.490	
				w/o comp notch			3.642	3.670	3.642	3.662	
100 HP	1987-93	4	RS	Straight Sleeve	3.375"		LA053	L053	1061SA	1061SB	
115 HP	1989-93	4	CS	With Ports	86mm		5.775	5.775	5.775	5.775	
				w/Power Port			3.644	3.670	3.642	3.662	
							(RS Sleeve)	(CS Sleeve)			
100 HP	1994-04	4	RS	Straight Sleeve	3.500"			L131	1075SA	1075SB	
115 HP 1848cc				With Ports	89mm			5.770	5.770	5.770	
125 HP				w/o exh notch				3.766	3.765	3.785	
100 HP	1968-71	6	CI	Straight Sleeve	2.937"	T215	LA215	L215			
65 HP				No Ports		5.00	5.00	5.00			
Crossflow						3-1/16"	3-1/8"	3-3/16"			
115 HP	1984-88	6	CI	Straight Sleeve	2-7/8"	T048		L048	1042SA	1042SB	
				With Ports		4-7/8"		4-7/8"	4.875	4.875	
				w/o power port		3.00		3-1/8"	3.003	3.128	
115 HP	1970-81	6	CI	Straight Sleeve	2-7/8"	T016		L016	1020SA	1020SB	
				with ports		4-7/8"		4-7/8"	4.875	4.875	
				w/o power port		3.00		3-1/8"	3.003	3.128	
115 HP	1982-88	6	CI	Straight Sleeve	2-7/8"	T017		L017	1021SA	1021SB	
140 HP	1978-81	6		with ports		4-7/8"		4-7/8"	4.875	4.875	
150 HP	1973-78	6		w/Power Port		3.00		3-1/8"	3.003	3.128	
115 HP	1999-00	V6	RS	Straight Sleeve	3.500"		LA177				
135 HP	1998-04	V6		with ports	89mm		5.275				
2507cc (153 C.I.)							3.693				
120 HP SportJet	1996		CI	Straight Sleeve	3.375"	T70	LA70	L70	1049SA	1049SB	104980
				without ports	86mm	5.550	5.550	5.550	5.510	5.510	5.510
						3-1/2"	3-9/16"	3-5/8"	3.500	3.563	3.625
135 HP	1998-04	V6	RS	Straight sleeve	3.500"		LA172		1132SA		
2.5L Optimax				with ports	89mm		5.275		5.275		
							3.693		3.693		
135 HP	1996-00	V6	CI	Straight Sleeve	3-1/8"		LA04	L04	1026SA	1026SB	
150 HP V-1500	thru 1998			with ports			5.550	5.550	5.545	5.545	
175 HP V-1750	thru 1981						3-5/16"	3-3/8"	3.313	3.375	
135 HP	1996-00	V6	CI	Flanged Sleeve	3-1/8"			FL04	1026FA		
150 HP V-1500	thru 1998			with ports				5.550	5.545		
175 HP V-1750	thru 1981							3.315	3.313		

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS** Denotes Replacement Sleeve
 - CI Denotes Cast in Sleeve Liner

- ② Oversizes Available
 - **CC** Denotes Original Barrel is Cast Iron
 - **CS** Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



	MERCLIRY	CAT	IND	ER SLEEVES			LA Sleeve		Adv	DSA 1070SB 55 5.355 57 3.577		
	WILKCONT	CIL	שווו			1/16"Thick	3/32"Thick	1/8" Thick				
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length	
					Size	0.D.	O.D.	O.D.	O.D.	O.D.	O.D.	
2.0 Litre	1986-90	V6	AC	Straight Sleeve	3-1/8"		LA047	L047				
				with ports			5.520	5.520				
				w/ finger ports			3-5/16"	3-3/8"				
2.0 Litre	1991-92	V6	AC	Straight Sleeve	3-1/8"			L080				
Champ Racing Engine				with ports				5.265				
Bridged Exhaust				Bridged Exhaust				3.435				
2.0 Litre	1991-92	V6	AC	Straight Sleeve	3-1/8"			L098				
Longer Length				with ports				5.550				
Bridged Exhaust				Bridged Exhaust				3.435				
150 HP XR4	1990-92	V6	RS	Straight Sleeve	3-3/8"		LA054		1070SA	1070SB		
				with ports			5.344		5.355	5.355		
							3.557		3.557	3.577		
				Flanged Sleeve						1070FB		
				with ports						5.355		
										3.577		
150 HP XRi	1993	V6	RS	Straight Sleeve	3.500"		LA146					
2.5L				with ports	89mm		5.275					
				w/Exhaust Notch			3.693					
150 HP Optimax	1999-04	V6	RS	Straight Sleeve	3.500"		LA172			1132SA	1132SB	
2.5L				with ports	89mm		5.275			5.275	5.275	
				w/o ehx notch			3.693			3.693	3.713	
150 HP Optimax	1997-00	V6	RS	Straight Sleeve	3.500"				1143SA	1143SB		
2.5L				with ports	89mm				5.320	5.320		
With notch at bo	ttom of sleeve.	w/o e	· xhaus						3.693	3.713		
150 HP XR6	,		RS	Straight Sleeve	3.500"				1071SA	1071SB		
2.5L	1991-96			with ports	89mm				5.275	5.275		
				w/Exhaust Notch					3.693	3.710		
150 HP XR6	1994-04	V6	RS	Straight Sleeve	3.500"		LA079		1041SA	1041SB		
2.5L				with ports	89mm		5.275		5.275	5.275		
				'			3.693		3.693	3.710		
150 HP	1997-04	V6	RS	Straight Sleeve	3.500"		LA151		1095SA	1095SB		
				with ports	89mm		5.305		5.275	5.275		
				small exh notch			3.692		3.693	3.710		
150 HP	2000-03	V6	RS	Straight Sleeve	3.500"		5.302		1139SA	1139SB		
2.5L with O Ring				with ports	89mm				5.320	5.320		
Heads				w/exhaust notch & notch at bottor		e			3.693	3.713		
175 HP	1983-92	V6	AC	Straight Sleeve	3-3/8"	~	LA014	L014	1027SA	1027SB	1027SC	
	1000 02	"	, 10	with ports	0 0/0		5.550	5.550	5.550	5.550	5.550	
				w/finger ports			3-9/16"	3-5/8"	3.565	3.585	3.628	
AC Denotes Alloy-Ch	nama Oulle Is	. Dage		igor porto		② Oversize		3 0/0	J.000	0.000	3.020	

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS Denotes Replacement Sleeve**
 - CI Denotes Cast in Sleeve Liner

- 2 Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - **CS** Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



	MERCURY	CYL	IND	ER SLEEVES			LA Sleeve		Ad	vanced Sle	eve
						1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
		2/2			Size	0.D.	0.D.	0.D.	O.D.	O.D.	O.D.
175 HP	1983-92	V6	AC	Flanged Sleeve	3-3/8"			FL043	1027FA	1027FB	1027F
2.4L				with ports					5.550	5.550	5.550
				w/finger ports					3.565	3.585	3.628
175 HP XR4	1991-92	V6	RS	Straight Sleeve	3-3/8"		LA103		1146SA	1146SB	
2.4L				with ports			5.384				
		-		Sleeve length +.030			3.557		3.557	3.577	
175 HP XRi	1991-95	V6	RS	Straight Sleeve	3.500"		LA079		1041SA	1041SB	1041S
2.5L				with ports	89mm		5.275		5.275	5.275	5.275
							3.693		3.693	3.710	3.733
										1041SB+1	
										3.720	
				Flanged sleeve		FL081			1041FA	1041FB	
				with ports		5.270			5.275	5.275	
						3.710			3.693	3.710	
175 HP XR2	1996-04	V6	RS	Straight Sleeve	3.500"		LA151		1095SA	1095SB	1095S
2.5L				with ports	89mm		5.305		5.275	5.275	
				small exh notch			3.692		3.693	3.710	
175 HP Optimax	1999-04	V6	RS	Straight Sleeve	3.500"		LA172			1132SA	1132S
2.5L				with ports	89mm		5.275			5.725	5.275
				w/o exh relief notch			3.693			3.693	3.713
175 HP	2000-04	V6	RS	Straight Sleeve	3.500"				1138SA	1138SB	
2.5L				with ports	89mm				5.320	5.320	
O-Ring Head				w/Exhaust Notch					3.693	3.703	
V-2000 200 HP	thru 1982	V6	AC	Straight Sleeve	3-3/8"		LA05	L05	1048SA	1048SB	1048S
V-2250 225 HP	thru 1982			with ports			5.550	5.550	5.550	5.550	5.550
2.4L							3-9/16"	3-5/8"	3.565	3.585	3.628
V-2000 200 HP	thru 1982	V6	AC	Flanged Sleeve	3-3/8"		FL06		1048FA		
V-2250 225 HP	thru 1982			with ports			5.550		5.550		
2.4L							3-9/16"		3.565		
V2000 200 HP	1982-83	V6	AC	Straight Sleeve	3-3/8"		LA014	L014	1027SA	1027SB	102750
200 HP EFI	1983-90			with ports			5.550	5.550	5.550	5.550	5.550
2.4L				w/ finger ports			3-9/16"	3-5/8"	3.565	3.585	3.628
V2000 200 HP	1982-83	V6	AC	Flanged Sleeve	3-3/8"		FL043		1027FA	1027FB	1027F0
200 HP EFI	1983-90			with ports			5.550		5.550	5.550	5.550
2.4L				w/ finger ports			3-9/16"		3.565	3.585	3.628
200 HP EFI	1983-90	V6	AC	Straight Sleeve	3-3/8"		LA073	L073	1044SA	1044SB	104450
200 HP	1982-90			with ports. Same as LA014	1 2.2		5.410	5.410			
2.4L				but, shorter length			3-9/16"	3-5/8"	3.565	3.585	3.628
200 HP	1986-87	V6	AC	Straight Sleeve	3-3/8"			- 37 -	1151SA	. ,	
2.4L				with ports	50,0						
				porto					3.565		
200 HP	1987-91	1/6	AC	Straight Sleeve	3-3/8"		LA055		1114SA	1114SB	111480
2.4L	1901-91	100	AU	with ports	3-3/0		5.550		5.410	5.410	5.410
4.7L				with ports			3-9/16"		5.410	3.410	0.410

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS Denotes Replacement Sleeve**
 - CI Denotes Cast in Sleeve Liner

- Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - **CS** Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



with ports 1999-UP V6 RS Straight Sleeve with ports 10 oring head					LA Sleeve		Adv	vanced Sle	eve		
	WIERCURY	CYL	טוח.			1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	0.D.	O.D.	O.D.	O.D.	0.D.	O.D.
200 HP	1996-00	V6	RS	Straight Sleeve	3.500"		LA165		1092SA	1092SB	1092SC
2.5L				with ports			5.275		5.275	5.275	5.275
							3.693		3.693	3.710	3.730
200 HP	1999-UP	V6	RS	Straight Sleeve	3.500"		LA181		1124SA	1124SB	1124SC
2.5L				with ports			5.310		5.320	5.320	5.320
w/ O ring head							3.693		3.693	3.713	3.733
200 HP	2000-04	V6	RS	Straight Sleeve	3.500"				1149SA	1149SB	
2.5L				with ports					5.320	5.320	
				small hole below intake					3.693	3.713	
200 HP DFI	1998-00	V6	RS	Straight Sleeve	3.625"				1148PSA	1148PSB	
3.0L Optimax				with ports					1148SSA		
Has 1/8" hole in sleeve.				w/o comp relief notch					3.884	3.906	
220 HP Laser Xri	1989-91	V6	AC	Straight Sleeve	3-3/8"		LA072	L072	1077SA	1077SB	
2.4L				with ports	0.00		5.550	5.550			
				w/ narrow finger ports			3-9/16"	3-5/8"	3.565	3.585	
220 HP Laser Xri	1989-91	V6	AC	Flanged Sleeve	3-3/8"		FL077		0.000		
2.4L			'	with ports and	0 0/0		5.500				
				narrow finger ports			3-9/16"				
225 HP	1978-82	V6	AC	Straight Sleeve	3.375"		LA055	L05	1048SA	1048SB	1048SC
2.4L	1570 02	0	7.0	with ports	0.070		5.550	5.550	5.550	5.50	5.550
2.7L				w/o boost ports			3-9/16"	3-5/8"	3.565	3.585	3.628
2.4L Bridged	1987-91	V6	AC	Straight Sleeve	3-3/8"		LA055	3-3/0	1047SA	1047SB	1047SC
Exhaust	1907-91	VO	AC	_	3-3/0		5.550				5.550
Exilaust				with ports			3-9/16"		5.550 3.565	5.550 3.585	3.628
2.41 Bridged Eybougt	1007.01	V6	۸.	Flanged Classes	3-3/8"		5-9/16 FL056		3.505 1047FA	3.363 1047FB	3.020
2.4L Bridged Exhaust	1987-91	Vo	AC	Flanged Sleeve	3-3/8						
				with ports			5.550		5.550	5.550	
0 EL 000 LID VD: EEL	4000.04	1/0	D0	Oraciala da casa	0.500		3-9/16"	1.070	3.565	3.585	404400
2.5L 200 HP XRi, EFI	1992-04	V6	RS	Straight sleeve	3.500"		LA079	L079	1041SA	1041SB	1041SC
				with ports	89mm		5.275	5.275	5.275	5.275	5.275
		110					3.693		3.693	3.710	3.733
2.5L 200 HP XRi, EFI	1992-04	V6	RS	Flanged sleeve	3.500"			FL081	1041FA	1041FB	
				with ports	89mm			5.275	5.275	5.275	
		+						3.710	3.693	3.710	
2.5L 200 HP	1996-04	V6		Straight sleeve				L153			
(original sleeve			AC	with ports				4.925			
is aluminum)		4						3.825			
2.5L 200 HP EFI	2000-04	V6	RS	Straight sleeve	3.500"		LA181		1124SA	1124SB	1124SC
"O" Ring Head				with ports	89mm		5.310		5.320	5.320	5.320
		_					3.693		3.693	3.713	3.733
3.0L 200 HP DFI	1998-04	V6	RS	Straight sleeve	3.625"			L154	1178PSA	1178PSB	
Ontimov				with ports	92mm			6.197	1178SSA	1178SSB	
Optimax				w/ comp relief notch	0=						

- AC Denotes Alloy-Chrome Cylinder Bore
 - **RS** Denotes Replacement Sleeve
 - CI Denotes Cast in Sleeve Liner

- ② Oversizes Available
 - **CC** Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.

Production of the second secon

Mercury Cylinder Sleeves

Model / HP	MERCURY CYLINDER SLEEVES Model / HP Year Cyl Type Notes						3/32"Thick	1/8" Thick			
	Year	انما				1/16"Thick	3/32 HINCK	1/0 THICK			
2.5L EFI		Cyl	Type	Notes	Bore	Length	Length	Length	Length	Length	Length
2.5L EFI					Size	0.D.	0.D.	0.D.	O.D.	O.D.	O.D.
	1991-92	V6	AC	Straight sleeve	3.500"			L096	1053SA	1053SB	105350
2.5L MOD VP	1991-92			with ports	89mm			4.896			
Nikasil Block								3.850	3.821	3.841	3.861
2.5L EFI	1991-92	V6	AC	Flanged sleeve	3.500"			FL099	1053FA	1053FB	
2.5L MOD VP	1991-92			with ports	89mm			4-7/8"			
Nikasil Block								3.850	3.821	3.841	
3.0L 200 HP EFI	1998-04	V6	RS	Straight sleeve	3.625"			L184	1178PSA	1178PSB	
Optimax				with ports	92mm			6.197	1178SSA	1178SSB	
				w/o exh notch				3.886	3.884	3.904	
3.0L 225HP	1994-98	V6	RS	Straight sleeve	3.625"				1073SA	1073SB	
				with ports	92mm				6.195	6.195	
				w/o exh notch					3.884	3.904	
3.0L 225HP	1994-00	V6	RS	Straight Sleeve,	3.625"			L132			
				with ports	92mm			6.197"			
				with exh notch				3.886"			
3.0L 225 HP DFI	1999-01	V6	RS	Straight sleeve	3.625"				1164SA	1164SB	
Optimax		'		with ports	92mm						
· p				w/o comp relief notch	02						
3.0L 225 HP DFI	2001-04	V6	RS	Straight sleeve	3.625"		(PORT)	L182	1181PSA	1181PSB	
3.0L 250 HP DFI	2001-04	1	110	with ports	92mm		(STBD)	L183		1181SSB	
Optimax	2001 04			1/8" hole below	JZIIIII		(0100)	6.197	6.195	6.195	
Оринах				intake ports				3.886	3.884	3.904	
225 HP Promax	1998-04	V6	DC	Straight sleeve	3.500"		LA165 @	3.000	1092SA	1092SB	109280
2.5L	1990-04	VO	K3		89mm		5.275		5.275	5.275	5.275
2.3L				with ports	09111111						
040 UD	0000	1/0		Ota-i-da al-a	0.500		3.693		3.693	3.710	3.730
240 HP	2000	V6	K5	Straight sleeve	3.500"		LA175		1124SA	1124SB	112450
2.5L				with ports	89mm		5.335		5.320	5.320	5.320
0.45.UD	4000.00	1/0		0	0.500		3.694	1.450	3.693	3.713	3.733
245 HP	1996-00	V6		Straight sleeve	3.500"			L153			
2.5L			AC	with ports	89mm			4.925			
260 HP	1996-00			(original sleeve is aluminum)				3.825	_		
3.0L 250 HP	1994-00	V6	RS	Straight sleeve	3.625"				1073SA	1073SB	
				with ports	92mm				6.195	6.195	
									3.884	3.904	
3.0L 250hp	1994-00	V6	RS	Straight Sleeve	3.625"			L132			
				With Ports	92mm			6.197"			
				With Exhaust Notch				3.886"			
250 XS 3.0L		V6	RS	Straight sleeve	3.625"				1175PSA	1175PSB	
				with ports	92mm				1175SSA	1175SSB	
3.0L 250 HP	2000	V6	RS	Straight sleeve	3.625"				1148SA	1148SB	
XB EFI				with ports	92mm				3.884	3.904	
3.0L 250 HP	2001	\/6	RS	Straight sleeve	3.625"				1154SA	1154SB	
J.OL 200 III	2001	100	110	with ports	92mm				113434	110400	
				w/o comp relief notch	92111111				3.884	3.904	

① AC Denotes Alloy-Chrome Cylinder Bore

- **RS** Denotes Replacement Sleeve
- CI Denotes Cast in Sleeve Liner

- ② Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.



	MERCURY	י כאו	חואו	ER SLEEVES			LA Sleeve		Adv	vanced Sle	eve
	IVILICONT	CIL	ישאוו.			1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	0.D.	0.D.	O.D.	O.D.	O.D.	0.D.
260 HP	1991-97	V6	RS	Straight sleeve	3.500"		L096		1053SA	1053SB	1053SC
2.5L Offshore				with ports			4.896				
							3.850		3.821	3.841	3.861
				Flanged Sleeve			FL099		1053FA	1053FB	1053FC
				wih ports			4-7/8"				
							3.850		3.821	3.841	3.861
				Straight sleeve with ports					1128SA	1128SB	1128SC
				Aluminum sleeve without							
				plating. Must have plated							
				after installation.					3.821	3.841	3.861
				Straight sleeve with ports					1117SA	1117SB	1117SC
				Aluminum sleeve with plating.							
				Must use diamond					3.821	3.841	3.861
				honing stones							
3.4L 275 HP		V6	AC	Straight sleeve	3.740"		LA015	L015			
1983-85, 1988-89				with ports	95mm		6.700	6.700			
							3-15/16"	4.00	3.945	3.965	
3.4L 250-275 HP	1990-93	V6	AC	Straight sleeve	3.740"		LA097		1099SA	1099SB	
				with ports	95mm		6.700		6.700	6.700	
							3-15/16"		3.945	3.965	
280 HP	1998-04	V6		Straight sleeve	3.500"				1100SA	1100SB	1100SC
				with ports							
				Nikasil					3.821	3.841	3.861
				Straight sleeve with ports)— — — — — — — — — — — — — — — — — — —			1134SA	1134SB	1134SC
				Aluminum sleeve without							
				plating. Must have plated					3.821	3.841	3.861
				after installation.							
				Straight sleeve with ports)— — — — — — — — — — — — — — — — — — —			1129SA	1129SB	1129SC
				Aluminum sleeve with plating.							
				Must use diamond					3.821	3.841	3.861
				honing stones							
300 HP Promax	1998-00	V6	RS	Straight sleeve	3.625"			L166	1152SA	1152SB	
				with ports	92mm			6.197	6.195	6.195	
Will not fit 300X				w/o comp relief notch				3.886	3.884	3.904	
300 Promax	2001-04	V6	RS	Straight sleeve	3.625"				1160SA	1160SB	
				with ports	92mm						
				w/o comp relief notch					3.884	3.904	
200 V	2001-04	V6	RS	Straight sleeve	3.625"				1163SA	1163SB	
300 X	2001-04	10									
300 X	2001-04	100		with ports	92mm				6.195	6.195	

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS Denotes Replacement Sleeve**
 - CI Denotes Cast in Sleeve Liner

- 2 Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.

Proposition of the second seco

Mercury Cylinder Sleeves

	MERCLIRV	, CAI	INIDI	ER SLEEVES			LA Sleeve		Advanced Sleeve		
	IVILICONI					1/16"Thick	3/32"Thick	1/8" Thick			
Model / HP	Year	Cyl	Туре	Notes	Bore	Length	Length	Length	Length	Length	Length
					Size	0.D.	0.D.	0.D.	O.D.	O.D.	0.D.
3.0L 300X HP	2001-04	V6	RS	Straight sleeve	3.625"				1163SA	1163SB	
Pro Max X Motor				with ports					6.195	6.195	
				w/o comp relief notch					3.884	3.904	
300 HP	1995-04	V6	RS	Straight sleeve	3.500"			L164	1082SA	1082SB	1082SC
S3000 RACE			AC	with ports	89mm			4.950	4.915	4.915	4.915
								3.850	3.821	3.841	3.861
				Straight sleeve with ports					1131SA	1131SB	1131SC
				Aluminum sleeve without							
				plating. Must have plated					3.821	3.841	3.861
				after installation.							
				Straight sleeve with ports					1120SA	1120SB	1120SC
				Aluminum sleeve with plating.							
				Must use diamond					3.821	3.841	3.861
				honing stones							

- ① AC Denotes Alloy-Chrome Cylinder Bore
 - **RS Denotes Replacement Sleeve**
 - CI Denotes Cast in Sleeve Liner

- 2 Oversizes Available
 - CC Denotes Original Barrel is Cast Iron
 - CS Denotes Cast in Sleeve

Be Sure to wash the block with soap and water after honing. The stones will leave a very fine grit in the motor. This grit will wear the rings and walls very fast. Solvent will not wash all the grit off, so you must use soap and water. Then apply 2 cycle oil on the cylinder walls to prevent rust

ALWAYS WAIT UNTIL THE SLEEVE ARRIVES BEFORE BEGINNING ANY MACHINE WORK. Never assume that the stated model and year of the cylinder is correct. Always check to see if the sleeve ports match the cylinder ports.